



US009409197B2

(12) **United States Patent**
Gehrung

(10) **Patent No.:** **US 9,409,197 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

- (54) **AIR NOZZLE CLOSURE FOR A SPRAY GUN**
- (71) Applicant: **SATA GmbH & Co. KG**, Kornwestheim (DE)
- (72) Inventor: **Ralf Gehrung**, Stuttgart (DE)
- (73) Assignee: **SATA GmbH & Co. KG**, Kornwestheim (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/572,998**

(22) Filed: **Dec. 17, 2014**

(65) **Prior Publication Data**
US 2015/0165463 A1 Jun. 18, 2015

(30) **Foreign Application Priority Data**
Dec. 18, 2013 (DE) 20 2013 105 779 U

- (51) **Int. Cl.**
B05B 1/28 (2006.01)
B05B 15/02 (2006.01)
B05B 15/06 (2006.01)
F16B 21/18 (2006.01)
- (52) **U.S. Cl.**
CPC **B05B 15/02** (2013.01); **B05B 15/065** (2013.01); **F16B 21/186** (2013.01)
- (58) **Field of Classification Search**
CPC B05B 15/02; B05B 15/06; B05B 15/065; B05B 3/1092; B05B 5/0426
USPC 239/290, 291, 600
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

40,433 A	10/1863	Sees
327,260 A	9/1885	Hart
459,432 A	9/1891	Anderson
459,433 A	9/1891	Avery
548,816 A	10/1895	Paul

(Continued)

FOREIGN PATENT DOCUMENTS

AT	153883	6/1997
AT	163577	3/1998

(Continued)

OTHER PUBLICATIONS

International Search Report (dated Jun. 20, 2008), Written Opinion (dated Jun. 20, 2008), and International Preliminary Report on Patentability (dated Sep. 14, 2010) from PCT/US2008/03318 filed Mar. 12, 2008.

(Continued)

Primary Examiner — Davis Hwu

(74) *Attorney, Agent, or Firm* — Paul D. Bianco; Gary Winer; Fleit Gibbons Gutman Bongini & Bianco PL

(57) **ABSTRACT**

An air nozzle closure for a spray gun with an air cap, which has at least one axial borehole for the passage of exiting air and a first annular flange, which is radially directed outward, and an air nozzle ring surrounding the air cap, with a second annular flange radially directed inward, and an inside thread for the screwing on of the air nozzle closure with an outside thread of the spray gun. The air cap in the screwed state, with annular flanges adjacent to one another, is clamped in between the spray gun and the air nozzle ring, and a first annular groove with a locking ring, which secures the air nozzle ring in the unscrewed state against the loosening of the air cap. The locking ring has at least one elastic snap-in element projecting inward to snap into the annular groove.

11 Claims, 3 Drawing Sheets

